

K O (H [•]

LEDITION | BAS(EDITION

LIGHTING 2008



T2 Panel

Panel luminaire with T2 light source, 2000 mm lead with 7.5 mm round plug.

Height: 15 mm

Length:

13 Watt | 710 mm

21 Watt | 1010 mm

23 Watt | 1110 mm

Projection: 48 mm

For connecting to 230 Volt supply
(note plug system)

Rating: 13, 21, 23 Watt/ 230 Volt

Colours: titanium, chrome



T2 Top

Surface luminaire with T2 light source, 2000 mm lead with mini plug.

Height: 40 mm

Length:

13 Watt | 710 mm

21 Watt | 1010 mm

23 Watt | 1110 mm

Projection: 50 mm

For connecting to 230 Volt supply
(note plug system)

Rating: 13, 21, 23 Watt/ 230 Volt

Colours: titanium, chrome

T2 Corpus luminaire

Corpus luminaire with T2 light source, complete with 2 luminaire holders for mounting to insides of corpus (by staple tacking), 2 x 1000 mm lead with mini HV AMP plug, white / loose.

Depth: 33 mm

Height: 19 mm

Length:

8 Watt | min. 405 mm - max. 1000 mm

11 Watt | min. 510 mm - max. 1000 mm

13 Watt | min. 610 mm - max. 1000 mm

For connecting to special electronic ballast for
"Twin Line"

Light colour: white

Colours: anodised aluminium, chrome





Run 1 W / 350 mA

Recessed spotlight with power LED, 2000 mm lead with black LED plug.

Outside diameter: 70 mm
Bore diameter: \varnothing 56 – 60 mm
Recessed depth: 16 mm

Rating: 1 Watt/ 350 mA
Light colours: white, warm colour
Colours: titanium, chrome, gold



Run 3 W / 700 mA

Recessed spotlight with power LED, 2000 mm lead with black LED plug.

Outside diameter: 70 mm
Bore diameter: \varnothing 56 – 60 mm
Recessed depth: 16 mm

Rating: 3 Watt/ 700 mA
Light colours: white, warm colour
Colours: titanium, chrome, gold



Run R 2,5 W / 12 Volt DC

Recessed spotlight with power LED, 2000 mm lead with white LED plug.

Outside diameter: 70 mm
Bore diameter: \varnothing 56 – 60 mm
Recessed depth: 16 mm

Rating: 2.5 Watt/ 12 Volt DC
Light colours: white, warm colour
Colours: titanium, chrome, gold



Run SMD 2,5 W / 12 Volt DC

Recessed spotlight with 9 LEDs, 2000 mm lead with white LED plug.

Outside diameter: 70 mm
Bore diameter: \varnothing 56 – 60 mm
Recessed depth: 16 mm

Rating: 2.5 Watt/ 12 Volt DC
Light colours: white, warm colour
Colours: titanium, chrome, gold



Lola Base Top 1
Lola Power Top 1

Surface luminaire with transparent light edge, 1000 mm lead with white LED plug.

Height: 28 mm
Width: 90 mm
Projection: 105 mm

Lola Base Top 1 | 0.9 Watt
Lola Power Top 1 | 2.5 Watt

For connecting to electronic ballast, 12 Volt DC
Light colour: white
Colour: chrome



Rio R, surface/under-surface

Surface and under-surface luminaire with power LED 2.5 Watt, 2000 mm lead with white LED plug, ball head can be angled in every direction (20°).

Height: 25 mm
Projection: 136 mm
Width: 46 mm
Length: 200 mm

Light colour: white
Rating: 2.5 Watt/ 12 Volt DC
Colours: titanium, chrome
Complete with 2 spacing blocks



Lola Base U
Lola Power U

Under-surface luminaire with transparent light edge, 1000 mm lead with white LED plug.

Height: 6.5 mm
Width: 88 mm
Length: 88 mm

Lola Base U | 0.9 Watt
Lola Power U | 2.5 Watt

For connecting to electronic ballast, 12 Volt DC
Light colour: white
Colour: chrome



Surf R

Surface and under-surface luminaire with power LED 2.5 Watt, 2000 mm lead with white LED plug.

Height: 22 mm
Projection: 136 mm
Width: 46 mm
Length: 200 mm

Light colour: white
Rating: 2.5 Watt/ 12 Volt DC
Colours: titanium, chrome
Complete with 1 spacing block



Smart Rim

Cold cathode surface luminaire with rim mounting bracket at rear, 2000 mm lead with JST plug.

Length: 352 mm
Width: 26 mm
Projection: 21 mm

For connecting to "Smart-Line" special electronic ballast

Colours: titanium, chrome



Smart Panel

Cold cathode surface luminaire with side spacing blocks and fixing holes with cover caps, 200 mm lead with JST plug.

Length: 370 mm
Width: 26 mm
Projection: 26 mm

For connecting to "Smart-Line" special electronic ballast

Colours: titanium, chrome



Smart Top

Cold cathode surface luminaire with 2 mounting brackets, 200 mm lead with JST plug.

Length: 352 mm
Width: 26 mm
Projection: 42 mm

For connecting to "Smart-Line" special electronic ballast

Colours: titanium, chrome



Plano

Recessed luminaire, 6 Watt Micro Lynx, 2000 mm lead with 7.5 mm round plug.

Bore diameter: \varnothing 80 mm
Recessed depth: 26 mm

Voltage: 230 Volt
Colours: titanium, chrome, brass

To match: High-voltage connecting lead, 4000 mm, with Europlug and HV mini 6-socket round-plug strip Art. No. 506273



Vario Rim

LED linear rim luminaire with rim mounting bracket at rear, 2000 mm lead with white LED plug.

Length:

352 mm with 18 LEDs | 1.8 Watt

352 mm with 9 LEDs | 0.9 Watt

650 mm with 36 LEDs | 3.6 Watt

650 mm with 18 LEDs | 1.8 Watt

Height: 26 mm

Projection: 21 mm

Voltage: 12 Volt DC

Light colours: white, warm colour

Colours: titanium, chrome



Vario Panel

LED linear surface luminaire with side spacing blocks and fixing holes with cover caps, 2000 mm lead with white LED plug.

Length:

370 mm with 18 LEDs | 1.8 Watt

370 mm with 9 LEDs | 0.9 Watt

670 mm with 36 LEDs | 3.6 Watt

670 mm with 18 LEDs | 1.8 Watt

Height: 26 mm

Projection: 26 mm

Voltage: 12 Volt DC

Light colours: white, warm colour

Colours: titanium, chrome



Vario Top

LED linear surface luminaire with 2 mounting brackets, 2000 mm lead with white LED plug.

Length:

352 mm with 18 LEDs | 1.8 Watt

352 mm with 9 LEDs | 0.9 Watt

650 mm with 36 LEDs | 3.6 Watt

650 mm with 18 LEDs | 1.8 Watt

Height: 26 mm

Projection: 42 mm

Voltage: 12 Volt DC

Light colours: white, warm colour

Colours: titanium, chrome



Flat R

Surface and under-surface luminaire with transparent diaphragm, white power LED 2.5 Watt, 2000 mm lead with white LED plug.

Height: 13 mm
 Length: 200 mm
 Width: 40 mm
 Projection: 136 mm

Rating: 2.5 Watt/ 12 Volt DC
 Colours: titanium, chrome



Flash

Recessed spotlight with control, white power LED 2.5 Watt, 2000 mm lead with white LED plug.

Outside diameter: 45 mm
 Bore diameter: \varnothing 40 mm
 Recessed depth: 12.5 mm

Rating: 2.5 Watt/ 12 Volt DC
 Colours: titanium, chrome



Carree

Recessed luminaire with 3 white SMD LEDs, 2000 mm lead with white LED plug.

Length: 70 mm
 Width: 70 mm
 Bore diameter: \varnothing 56 mm
 Recessed depth: 7 mm

Rating: 0.3 Watt/ 12 Volt DC
 Colour: brushed stainless steel



Point 50 Deko

Recessed spotlight with decorative trim, white power LED 1 Watt, 2000 mm lead with black LED plug.

Recessed depth: 12.5 mm
 Height: 4.5 mm
 Bore diameter: \varnothing 35 mm

Rating: 1 Watt/ 350 mA
 Colours: titanium, chrome



Cross Flex

Power LED reading lamp, 8 Watt, 400 mm flex hose, dia. 9 mm, 400 mm lead with white LED plug, 2 x 4 Watt power LEDs, soft-start, dimming and memory function, mounting bracket incl. cover.

Luminaire head length: 100 mm
Luminaire head width: 35 mm

Rating: 8 Watt/ 12 Volt DC
Colours: titanium, chrome

Also available as panel version



Loft

Glass flex lamp with power LED, 2.5 Watt, lamp glass optionally in the colour combinations black/white, white/white or black/bright, 450 mm flex hose chrome, dia. 9 mm, mounting bracket with integral microswitch and DC controller, 400 mm lead with white LED plug.

Luminaire head length: 55 mm
Luminaire head width: 30 mm

Rating: 2.5 Watt/ 12 Volt DC
Colour: chrome

■ WILHELM KOCH GMBH
KUPFERSTRASSE 22-24
D-33378
RHEDA-WIEDENBRÜCK
GERMANY

■ TEL.: +49 52 42 / 92 51-0
FAX: +49 52 42 / 92 51-99

■ E-MAIL:
POSTFACH@KOCH-LICHT.DE

■ INTERNET:
WWW.KOCH-LICHT.DE